



# LED Ambient Lighting

Combining a comfortable, pleasing atmosphere with energy efficiency is now possible with STANDARD's smooth dimming LED Ambient Lighting lamps. Choose from our large selection of lamp shapes and create your own style while saving on energy and maintenance costs.



| Order code   | Description                | Watts<br>(W) | Base | Volts<br>(VAC) | Color temp.<br>(K) | Finish | Life<br>L70<br>(hrs) | Lumen<br>output<br>(lm) | Traditional<br>equivalent<br>(W) | Case<br>qty<br>(inner/master) |
|--------------|----------------------------|--------------|------|----------------|--------------------|--------|----------------------|-------------------------|----------------------------------|-------------------------------|
| <b>A15</b>   |                            |              |      |                |                    |        |                      |                         |                                  |                               |
| 66758        | A15/S2/6W/27K/CL/STD       | 6            | E26  | 120            | 2 700              | Clear  | 15 000               | 514                     | 60                               | 24/48                         |
| 66759        | A15/S2/5.5W/27K/FR/STD     | 5.5          | E26  | 120            | 2 700              | Frost  | 15 000               | 496                     | 60                               | 24/48                         |
| 66760        | A15/S2/6W/30K/CL/STD       | 6            | E26  | 120            | 3 000              | Clear  | 15 000               | 592                     | 60                               | 24/48                         |
| 66761        | A15/S2/5.5W/30K/FR/STD     | 5.5          | E26  | 120            | 3 000              | Frost  | 15 000               | 511                     | 60                               | 24/48                         |
| 66762        | A15/S2/5.5W/40K/FR/STD     | 5.5          | E26  | 120            | 4 000              | Frost  | 15 000               | 530                     | 60                               | 24/48                         |
| <b>C12</b>   |                            |              |      |                |                    |        |                      |                         |                                  |                               |
| 66763        | C12/S2/4.5W/27K/CL/STD     | 4.5          | E26  | 120            | 2 700              | Clear  | 15 000               | 322                     | 40                               | 24/48                         |
| 66764        | C12/S2/4.5W/27K/E12/CL/STD | 4.5          | E12  | 120            | 2 700              | Clear  | 15 000               | 322                     | 60                               | 24/48                         |
| 66765        | C12/S2/4.5W/27K/E12/FR/STD | 4.5          | E12  | 120            | 2 700              | Frost  | 15 000               | 331                     | 60                               | 24/48                         |
| <b>G16.5</b> |                            |              |      |                |                    |        |                      |                         |                                  |                               |
| 66766        | G16.5/S2/5W/27K/E12/CL/STD | 5            | E12  | 120            | 2 700              | Clear  | 15 000               | 365                     | 60                               | 24/48                         |
| 66767        | G16.5/S2/5W/27K/E12/FR/STD | 5            | E12  | 120            | 2 700              | Frost  | 15 000               | 361                     | 60                               | 24/48                         |
| <b>G25</b>   |                            |              |      |                |                    |        |                      |                         |                                  |                               |
| 66768        | G25/S2/7W/27K/FR/STD       | 7            | E26  | 120            | 2 700              | Frost  | 15 000               | 553                     | 60                               | 24/48                         |
| 66769        | G25/S2/7W/30K/FR/STD       | 7            | E26  | 120            | 3 000              | Frost  | 15 000               | 553                     | 60                               | 24/48                         |

Lumen values are derived from photometric testing  
For a complete list of compatible dimmers, please visit [www.standardpro.com](http://www.standardpro.com)

