



ACCUBEAM

ACCUBEAM lamps use a reflector design that forms the light beam before it reaches the lens. The corrugated reflector allows for greater light concentration at the center of the beam providing a light output that is comparable to conventional halogens, while using less wattage. ACCUBEAM was designed to deliver a smooth, precise beam pattern and allows for even light distribution; without hot spots or striations.



MOL: 5.5/16 in. (138 mm)
Ø 4.3/4 in. (121 mm)

PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Beam angle (°)	Beam spread	Case qty (master)
PAR38									
50041 ¹	H45PAR38/FL/5M/130V/STD ACC	45	E26	130	390	5 000	30	Flood	15

¹ This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.



Reflector



MOL: 3 7/32 in. (82 mm)
Ø 2.5 in. (63.5 mm)

PAR20



MOL: 4 7/16 in. (113 mm)
Ø 7 in. (178 mm)

PAR56

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Beam angle (°)	Beam spread	Case qty (master)
PAR20										
69248	H35PAR20/NFL/2.5M/130V/STD S2	35	E26	130	300	2 500	2 850	30	Narrow Flood	20
PAR56										
43495	Q500PAR56MFL	500	GX16d	120	8 000	4 000	2 950	42	Flood	6
43496	Q500PAR56WFL	500	GX16d	120	8 000	4 000	2 950	66	Wide Flood	6



MOL: 5 5/16 in. (135 mm)
Ø 4 3/4 in. (121 mm)

PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (master)
PAR38											
10146 ¹	H60PAR38/CLB/5M/MS/130V/STD	60	E26	130	800	5 000	2 900	36	Flood	1 700	15

¹ This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.



ALR

ALR lamps are halogen aluminium reflector lamps. They are a lightweight and compact light source which are mainly used in display lighting, accent lighting, task lighting and in elevators.



Hgt. 1 17/32 in. (89 mm)
 D 1 1/2 in. (68 mm)

ALR12

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Finish	Beam angle (°)	Beam spread	Case qty (inner/master)
ALR12 - Cover Glass											
55062	20ALR12/F/FL/BA15d/12V/GBF STD	20	BA15d	12	750	2 000	3 000	Frost	32	Flood	20/100

