

Spécialité



T6



T7



ED37

Code de commande	Description	Forme	Culot	Code ANSI	Couleur temp. (K)	Flux lumineux (lm)	Lumens moyens (lm)	Vie moyenne (h)	IRC	Position de fonc.	Finition	Luminaire	Qté caisse (ext.)
70 watts													
57975	MH-DE 70W/UVS/4K STD	T6	R7s	M85/E	4 200	5 500	3 600	10 000	65	HOR±45°	Claire	E	25
68869	MH-DE 70W/UVS/3K STD	T6	R7s	M85/E	3 000	5 500	4 250	6 000	65	HOR±45°	Claire	E	144
150 watts													
59141	MH-DE 150W/UVS/3K STD	T7	R7s	M81/E	3 000	11 250	8 400	10 000	65	HOR±45°	Claire	E	25
360 watts													
68526	MPI360W/BU/EM STD	ED37	EX39	M165/M59/O	4 200	36 000	28 800	20 000	65	BU±15°	Clear	O	6

Halogénure métallique en céramique



T6



PAR30LN



T4.5

Code de commande	Description	Forme	Culot	Couleur temp. (K)	Vie moyenne (h)	Lumens initiaux (lm)	Lumens moyens (lm)	IRC	Position de fonc.	Finition	Luminaire	Qté caisse (ext.)
35 watts												
59993	CMH35PAR30LN/830/FL/STD	PAR30LN	E26	3 000	8 000	2 200	1 804	80	U	Claire	O	6
68875	CMT35/U/830/G12/STD	T6	G12	3 000	10 000	3 400	2 890	80	U	Claire	E	12
69171	CMT35/U/830/G8.5/STD	T4.5	G8.5	3 000	10 000	3 400	2 890	85	U	Clear	E	12
70 watts												
68876	CMT70/U/830/G12/STD	T6	G12	3 000	15 000	7 000	5 950	85	U	Claire	U	12

O = Luminaire intérieur ouvert E = Luminaire fermé pour intérieur ou extérieur
Note : Si la Description de la lampe contient UVS, la lampe possède la caractéristique anti-UV.