

COMPATIBLE DIMMERS FOR SILK¹

120 V, 120-277 V

Options		Dimmer		Surface ceiling				Pendant				Surface wall			
		Brand	Model	1 800 LM	2 500 LM	3 400 LM	5 000 LM	1 800 LM	2 500 LM	3 400 LM	5 000 LM	1 800 LM	2 500 LM	3 400 LM	5 000 LM
Standard	0-10 V driver, dims to 1%	Leviton	DD 710	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			DS 710	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
		Legrand	WS4FBL3P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
			RH4FBL3PTC	✓	✓	-	-	✓	✓	-	-	✓	✓	-	✓
		Lutron	DINA DVSTV	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
DIM2	Line voltage driver 120V, dims to 5%	Cooper	NOVA NTSTV DV	✓	✓	-	-	✓	✓	-	-	✓	✓	-	✓
			DAL06P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
			AAL06	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
		Leviton	SAL06P3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
			6615	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
			IPL06	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			6674	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			DSL06-1LZ	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			DSM10-1LZ	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			IPE04-1LZ	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			DDMX1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
		Legrand	RH730PTUTC	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			HCL453P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			PD-6WCL	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
			DVCL-153P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
			CTCL-153P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			DVCL-253P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			AYCL-253P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
			DVELV-300P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			SELV-300P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			MACL-153P	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

347 V

Options		Dimmer		Surface ceiling				Pendant				Surface wall			
		Brand	Model	1 800 LM	2 500 LM	3 400 LM	5 000 LM	1 800 LM	2 500 LM	3 400 LM	5 000 LM	1 800 LM	2 500 LM	3 400 LM	5 000 LM
Standard	0-10 V driver, dims to 1%	Leviton	IP 710	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
			NOVA NFTV	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

✓	Compatible
-	Not compatible

¹ This table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

OPERATING TEMPERATURES FOR SILK

Surface Ceiling & Pendant		Surface Wall	
120 V	- 1800, 2500, 5000 LM:	-20°C to 30°C (-4°F to 86°F)	- 1800 and 2500 LM: -20°C to 30°C (-4°F to 86°F)
	- 3400 LM:	-40°C to 30°C (-40°F to 86°F)	- 3400 LM: -40°C to 30°C (-40°F to 86°F)
	- 5000 LM:	-10°C to 30°C (14°F to 86°F)	- 5000 LM: -10°C to 30°C (14°F to 86°F)
120-277 V	- 1800 and 2500 LM:	-20°C to 30°C (-4°F to 86°F)	- 1800 and 2500 LM: -20°C to 30°C (-4°F to 86°F)
	- 3400 and 5000 LM:	-40°C to 30°C (-40°F to 86°F)	- 3400 and 5000 LM: -40°C to 30°C (-40°F to 86°F)
347 V	-40°C to 30°C (-40°F to 86°F)	-40°C to 30°C (-40°F to 86°F)	-40°C to 30°C (-40°F to 86°F)