

COMETO FIRE-RATED Slim Backlit Downlight

COMETO Fire-rated slim backlit downlight has been designed and tested to meet fire-resistance standards. The housing is made of heat-resistant reinforced steel, giving it a 2-hour fire-resistance rating. Suitable for all spaces required fire-rated downlight such as schools, hospitals, and public areas.



IC
rated



dimmable
fixture



Intertek



■ Designed for fire-resistant

The downlight housing and fixing screws are made of steel material. The 2 spring brackets are fully welded, and the power cable support has a steel cover on top to prevent burning a small area and the fire from reaching the inside of the ceiling.

■ No additional hardware

With COMETO Fire-rated downlight no need to add a fire-rated steel box or dome to cover the downlight and, it can be used on its own. Save on installations and cost.

■ Color selectable

The switch is directly placed on the back of the LED module to select from 5 color temperature (2 700/3 000/3 500/4 000/5 000 K). Gives you more choice for your lighting projects and application.

Designed for resistance - 2 hour fire rated!

- Available in round 4" and 6"



- 2-hour fire-resistant steel housing
Tested and conformed with UL 263, ASTM E119, CAN/ULC S101 and ANSI/UL 263

- Frosted polycarbonate lens providing 100° beam angle

- CCT selectable switch is discretely placed on the back of the LED module




- FT6 cable rating

- Spring mounting clips for easy installation

Compatible accessories


Select from a variety of accessories for different installation options!



Mounting plate with hanger bars



Adjustable mounting plate



Square mounting plate



Vapor barrier extender



6' extension cord