

DOUBLE RING 5 CCT SELECTABLE LED Ceiling Luminaire

Our Double Ring LED Ceiling Luminaire series is a simple and convenient lighting solution. Available in different sizes, this luminaire is an excellent choice to add a decorative touch to any residential or commercial applications such as hallways, bedrooms, lobbies and more!



■ Color Selectable

Versatile solution with an integrated 5 color temperature selection (2 700/3 000/3 500/4 000/5 000 K). Easily select the desired color temperature using the switch located inside the housing. An ideal solution for reducing stocking inventory.

■ Accentuate any space

With two decorative rings in either brushed nickel or black finish, our Double Ring luminaires will help accentuate any residential or commercial space.

■ Easily installed

Appreciate an easy installation and maintenance, simply unscrew the 3 nuts to remove the metallic ring and lens.

Adapt the color temperature to your needs!



Semi-flush suspension kit

The brushed nickel luminaire can be installed surface mounted (standard) or semi-flush mounted when used with the compatible semi-flush suspension kit sold separately as an accessory.



Specification Table

Order code	Model number	Watts	Volts	Color temp.	Lumen output	Efficiency	CRI	Life L70	Beam angle	Shape	Finish	Dimming	Power factor	Master case qty
		(W)	(VAC)	(K) ¹	(lm) ²⁻³	(lm/W)		(hrs) ⁴	(°)			(Yes/No)		
5 CCT Selectable														
12"														
68977	CLDR12-R15W-A-5CBN	15	120	2 700/3 000/3 500/4 000/5 000	1 250	83	80+	50 000	120	Round	Brushed Nickel	Yes	0.90	4
68980	CLDR12-R15W-A-5CBK	15	120	2 700/3 000/3 500/4 000/5 000	1 250	83	80+	50 000	120	Round	Black	Yes	0.90	4
14"														
68978	CLDR14-R25W-A-5CBN	25	120	2 700/3 000/3 500/4 000/5 000	1 735	69	80+	50 000	120	Round	Brushed Nickel	Yes	0.90	4
68981	CLDR14-R25W-A-5CBK	25	120	2 700/3 000/3 500/4 000/5 000	1 735	69	80+	50 000	120	Round	Black	Yes	0.90	4
16"														
68979	CLDR16-R25W-A-5CBN	25	120	2 700/3 000/3 500/4 000/5 000	1 735	69	80+	50 000	120	Round	Brushed Nickel	Yes	0.90	4
68982	CLDR16-R25W-A-5CBK	25	120	2 700/3 000/3 500/4 000/5 000	1 735	69	80+	50 000	120	Round	Black	Yes	0.90	4

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from Energy Star reported data. Initial lumens range: +/- 10 %.

⁴ Life hours are derived from IESNA LM-80-08 testing report and projected per IESNA TM-21-11 extrapolations.

Compatible accessories

Order code	Model number	Type	Finish	Diameter (in.)	Compatible with	Case qty (master)	Figure
68983	LEN-CLDR12	Lens	Frosted	10 3/4	68977, 68980	10	A
68984	LEN-CLDR14	Lens	Frosted	12 3/4	68978, 68981	5	A
68985	LEN-CLDR16	Lens	Frosted	14 1/2	68979, 68982	5	A
69747	6IN STEM SUSP. KIT WITH WIRE FOR CLDR BN	6" Semi-flush stem kit with ground wire extension	Brushed nickel	4 3/4 ¹	68977, 68978, 68979	50	B

¹ Mounting plate and canopy dimension.

