

PROJECT: DATE:

DISTRIBUTOR: CATALOGUE #: TYPE:

DRAWN BY: CONTRACTOR: PO:



STANPRO

SPEC SHEET

**SLIM PROFILE WITH 5 CCT SELECTABLE
VARIETY OF DECORATIVE MOUNTING ACCESSORIES**

FEATURES AND SPECIFICATIONS

CONSTRUCTION

Physical Characteristics

- Polycarbonate housing
Note: The back of the housing for 5" and 19" is galvanized iron
- Available sizes: 5", 7", 9", 12", 16" and 19"
- CCT selectable switch is placed at the back of the housing
- Frosted PMMA lens and PS diffuser
- Standard beam angle is 110°

Mounting

- Surface installation is standard for luminaires, easy twist-lock
- For additional surface or suspended installations, see compatible mounting kit accessories


PERFORMANCE DATA

- Available in 2 700/3 000/3 500/4 000/5 000 K selectable color temperature
- 80+ CRI
- Electrical ratings: 120 V
- Lumen output: 903-3 598 lm
- Phase cut (ELV / Triac) dimming standard
- Operating temperature: -10 °C to 45 °C (14 °F to 113 °F)

COMPLIANCES

- cETLus listed for Canada and USA for damp locations
- Energy Star for 5", 7" and 9" luminaires
- Meets requirements of ICES-005 issue 5

TECHNICAL DRAWINGS



Size	A	B	C	Net Weight (lbs)
5"	4 3/8" (11.1 cm)	5 1/4" (13.5 cm)	3/4" (1.8 cm)	0.45
7"	6 1/8" (15.5 cm)	7 1/8" (18 cm)	3/4" (1.8 cm)	0.49
9"	7 7/8" (19.9 cm)	8 7/8" (22.5 cm)	3/4" (1.8 cm)	0.65
12"	10 7/8" (27.5 cm)	11 3/4" (30 cm)	3/4" (1.8 cm)	1.17
16"	14 3/4" (37.4 cm)	15 3/4" (40 cm)	3/4" (1.8 cm)	2.65
19"	17 1/2" (44.35 cm)	18 7/8" (48 cm)	1 1/8" (2.85 cm)	2.87

* Please refer to the product web page to view detailed drawings by size.



5 CCT



5 YEARS
WARRANTY



ICES
005



ETL
Intertek



* Only on 5" 7" 9".

QUICK SHIP AND TECHNICAL SPECIFICATION TABLE

Type	Order Code	Model Number	Lumen Output (lm) ^{1,2,3}	Efficacy (lm/W)	Watts (W)	Life L70 (hrs) ⁴	Tested Hours LM-80 (hrs) ⁴	Finish	Power Factor	Master Case Qty	UPC
5"											
	70672 ²	CLCR5-R11W-A-5CWH	910	83	11	54 000	9 000	White	≥0.90	40	069549036505
7"											
	70673 ²	CLCR7-R12W-A-5CWH	1 000	83	12	54 000	9 000	White	≥0.90	40	069549036512
9"											
	70674 ²	CLCR9-R18W-A-5CWH	1 500	83	18	54 000	9 000	White	≥0.90	20	069549036529
12"											
	70675 ¹	CLCR12-R24W-A-5CWH	2 115	88	24	54 000	9 000	White	≥0.90	10	069549036536
16"											
	71428 ¹	CLCR16-R30W-A-5CWH	2 877	96	30	54 000	9 000	White	≥0.90	10	069549038837
	71429 ¹	CLCR16-R30W-A-5CBK	2 794	93	30	54 000	9 000	Black	≥0.90	10	069549038844
19"											
	71430 ¹	CLCR19-R36W-A-5CWH	3 226	90	36	54 000	9 000	White	≥0.90	4	069549038851
	71431 ¹	CLCR19-R36W-A-5CBK	3 128	87	36	54 000	9 000	Black	≥0.90	4	069549038868

¹ Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.² Lumen values are derived from Energy Star reported data. Initial lumens range: +/- 10 %.³ Lumen values are based on 3 000 K default programming. Please refer to the LUMEN SPECIFICATION TABLE for more details on other color temperatures.⁴ Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.

LUMEN SPECIFICATION TABLE

Order Code	Model Number	Watts (W)	2 700 K		3 000 K		3 500 K		4 000 K		5 000 K		Default Programming
			Lumen Output (lm)	Efficacy (lm/W)	Lumen Output (lm)	Efficacy (lm/W)	Lumen Output (lm)	Efficacy (lm/W)	Lumen Output (lm)	Efficacy (lm/W)	Lumen Output (lm)	Efficacy (lm/W)	
70672	CLCR5-R11W-A-5CWH	11	903	82	926	84	961	87	970	88	939	85	3 000 K
70673	CLCR7-R12W-A-5CWH	12	1 006	84	1 019	85	1 048	87	1 075	90	1 040	87	3 000 K
70674	CLCR9-R18W-A-5CWH	18	1 470	82	1 511	84	1 583	88	1 598	89	1 511	84	3 000 K
70675	CLCR12-R24W-A-5CWH	24	2 021	84	2 115	88	2 205	92	2 235	93	2 178	91	3 000 K
71428	CLCR16-R30W-A-5CWH	30	2 800	93	2 877	96	2 976	99	3 016	101	3 035	101	3 000 K
71429	CLCR16-R30W-A-5CBK	30	2 699	90	2 794	93	2 938	98	2 970	99	2 881	96	3 000 K
71430	CLCR19-R36W-A-5CWH	36	3 012	84	3 226	90	3 598	100	3 567	99	3 388	94	3 000 K
71431	CLCR19-R36W-A-5CBK	36	2 938	82	3 128	87	3 402	95	3 367	94	3 194	89	3 000 K

COMPATIBLE DIMMERS¹

Brand	5"	7"	9"	12"	16"	19"
	Model					
Lutron	HCL453P ² , PD-6WCL, DVCL-153P ² , CTCL-153P, AYCL-253P, DVELV-300P, SELV-300P, MACL-153P	HCL453P, PD-6WCL ² , CTCL-153P, DVCL-253P, AYCL-253P, DVELV-300P, SELV-300P, MACL-153P	HCL453P, PD-6WCL, CTCL-153P, DVCL-253P, AYCL-253P, DVELV-300P, SELV-300P, MACL-153P	HCL453P, PD-6WCL, CTCL-153P, DVCL-253P, AYCL-253P, DVELV-300P, SELV-300P, MACL-153P	HCL453P, PD-6WCL, DVCL-153P, CTCL-153P, DVCL-253P, AYCL-253P, DVELV-300P, SELV-300P, MACL-153P, DDMX1	HCL453P, PD-6WCL, DVCL-153P, CTCL-153P, DVCL-253P, AYCL-253P, DVELV-300P, SELV-300P, MACL-153P, DDMX1
Cooper	DAL06P, AAL06, SAL06P3	DAL06P, AAL06 ² , SAL06P3	DAL06P, AAL06, SAL06P3	DAL06P, AAL06, SAL06P3	DAL06P, AAL06, SAL06P3	DAL06P, AAL06, SAL06P3
Leviton	6615, IPL06, 6674, DSL06-1LZ, IPE04-1LZ, DDMX1	6615 ² , IPL06, 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ, DDMX1	6615, IPL06, 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ, DDMX1	6615 ² , IPL06, 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ, DDMX1	6615 ² , 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ	6615 ² , IPL06, 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ
Legrand	-	RH730PTUTC	RH730PTUTC	RH730PTUTC	RH730PTUTC	RH730PTUTC

Dimming range: 5 %-100 %

² 10 %-100 %¹ This table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

ACCESSORIES*

Order Code	Type	Finish	Diameter (in.)	Compatible With	Master Case Qty	Figure
70648	Clip-on trim	Matte black	5"	70672	40	A
70649	Clip-on trim	Satin nickel	5"	70672	40	B
70650	Clip-on trim	Matte black	7"	70673	40	A
70651	Clip-on trim	Satin nickel	7"	70673	40	B
70652	Clip-on trim	Matte black	9"	70674	40	A
70653	Clip-on trim	Satin nickel	9"	70674	40	B
70654	Clip-on trim	Matte black	12"	70675	20	A
70655	Clip-on trim	Satin nickel	12"	70675	20	B
70656	Decorative clip-on trim	Black/Gold	12"	70675	20	C
70657	Decorative clip-on trim	Black	12"	70675	20	D
71432	Decorative clip-on trim	Black/Gold	16"	71428, 71429	10	C
71433	Decorative clip-on trim	Black	16"	71428, 71429	10	D

* Order separately.



A



B



C



D

SMART ACCESSORIES*

Order Code	Description	Figure
70515	Bluetooth Phase Controller - Forward and Reverse 120V AC Genio	A

* Order separately.



A


CABLE SUSPENSION MOUNTING KIT ACCESSORIES¹

Order Code	Model Number	Cable Length (in.)	Finish	Compatible Luminaire (not included)	Master Case Qty	UPC	Figure
71434	10FT CABLE SUSPENSION WH FOR CLCR	120	White	All sizes ASTRA and CIRKA DECO	12	069549038899	A
71435	10FT CABLE SUSPENSION BK FOR CLCR	120	Black	All sizes ASTRA and CIRKA DECO	12	069549038905	B

¹ Compatible luminaire is not included in mounting kit accessory and needs to be ordered separately.



A




B

CYLINDER MOUNTING KIT ACCESSORIES¹

Order Code	Model Number	Diameter (in.)	Cable Length (in.)	Compatible Luminaire (not included)	Master Case Qty	UPC	Figure
Surface Cylinder							
70658	5IN CYL SURFACE KIT BLACK FOR CLCR5	5 3/8	-	70672	20	069549036369	A
70659	5IN CYL SURFACE KIT WHITE FOR CLCR5	5 3/8	-	70672	20	069549036376	A
Suspended Individual Cylinder							
70660	5IN CYL 10FT SUSP KIT BLACK FOR CLCR5	5 3/8	120	70672	16	069549036383	B
70661	5IN CYL 10FT SUSP KIT WHITE FOR CLCR5	5 3/8	120	70672	16	069549036390	B
Suspended Multi-Cylinder							
70662	MULTI CYL 10FT SUSP KIT BLACK FOR CLCR5	5 3/8	120	3x 70672	1	069549036406	C
70663	MULTI CYL 10FT SUSP KIT WHITE FOR CLCR5	5 3/8	120	3x 70672	1	069549036413	C

¹ Compatible luminaire is not included in mounting kit accessory and needs to be ordered separately.



PENDANT MOUNTING KIT ACCESSORIES¹

Order Code	Model Number	Diameter (in.)	Cable Length (in.)	Finish	Compatible Luminaire (not included)	Master Case Qty	UPC	Figure
Cone								
70664	16IN CONE 10FT SUSP KIT BLACK FOR CLCR9	15 3/4	120	Black	70674	2	069549036420	A
70665	16IN CONE 10FT SUSP KIT WHITE FOR CLCR9	15 3/4	120	White	70674	2	069549036437	A
70668	19IN CONE 10FT SUSP KIT BLACK FOR CLCR12	19 1/8	120	Black	70675	2	069549036468	A
70669	19IN CONE 10FT SUSP KIT WHITE FOR CLCR12	19 1/8	120	White	70675	2	069549036475	A
Dome								
70666	15IN DOME 10FT SUSP KIT BLACK FOR CLCR9	14 5/8	120	Black	70674	2	069549036444	B
70667	15IN DOME 10FT SUSP KIT WHITE FOR CLCR9	14 5/8	120	White	70674	2	069549036451	B
70670	18IN DOME 10FT SUSP KIT BLACK FOR CLCR12	17 7/8	120	Black	70675	2	069549036482	B
70671	18IN DOME 10FT SUSP KIT WHITE FOR CLCR12	17 7/8	120	White	70675	2	069549036499	B

¹ Compatible luminaire is not included in mounting kit accessory and needs to be ordered separately.

