



PAR Shapes, MR16 & GU10

Long Life

The PAR Shapes, MR16 & GU10 - Long Life LED lamps provide a cost-effective and sustainable lighting solution. In addition, they offer consistent color from lamp to lamp, ensuring a uniform look throughout your space. Choose from a variety of PAR options, including PAR16, PAR20, PAR30LN, PAR30SN and PAR38, as well as MR16 and GU10 options. Whatever your lighting needs, our Reflector Lamps provide the perfect solution.



MR11



MR16



MR16
3 CCT 25°



MR16
3 CCT 40°



GU10



GU10
5 CCT 25°



GU10
5 CCT 40°

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Case qty (master)
MR11												
64244 ¹	LED/MR11/4W/30K/38/GU4/ND/STD	4	GU4	12	3 000	80	25 000	260	38	550	30	48
MR16 CCT Selectable												
70169	MR16/6W/3CCT/25/STD	6	GU5.3	12	2 700/ 3 000/ 4 000	80	33 000	510	25	1 400	50	48
70170	MR16/6W/3CCT/40/STD	6	GU5.3	12	2 700/ 3 000/ 4 000	80	33 000	517	25	880	50	48
MR16												
68263	MR16/S2/7.5W/27K/25/STD	7.5	GU5.3	12	2 700	90	54 000	570	25	3 196	75	60
68259	MR16/S2/7.5W/27K/35/STD	7.5	GU5.3	12	2 700	90	50 000	570	35	1 908	75	60
68265	MR16/S2/7.5W/40K/25/STD	7.5	GU5.3	12	4 000	90	50 000	570	25	3 613	75	60
68261	MR16/S2/7.5W/40K/35/STD	7.5	GU5.3	12	4 000	90	50 000	570	35	2 066	75	60
GU10 CCT Selectable												
69729	GU10/6.5W/5CCT/25/STD	6.5	GU10	120	2 700/3 000/3 500/4 000/5 000	80	25 000	500	25	-	50	100
69626	GU10/6.5W/5CCT/40/STD	6.5	GU10	120	2 700/3 000/3 500/4 000/5 000	80	25 000	500	40	502	50	100
GU10												
68257	GU10/S2/6.5W/40K/35/STD	6.5	GU10	120	4 000	90	54 000	570	35	1 231	50	60

Lumen values are derived from photometric testing
For a complete list of compatible dimmers, please visit www.standardpro.com





PAR20
5 CCT



PAR30SN
5 CCT



PAR20



PAR30SN

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Case qty (master)
PAR20 CCT SELECTABLE												
69641 ^{2,3}	P20/6.5W/5CCT/25/STD	6.5	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	540	25	1 800	50	24
69642 ^{2,3}	P20/6.5W/5CCT/40/STD	6.5	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	540	40	1 100	50	24
PAR20												
68219	P20/S2/7W/27K/40/STD	7	E26	120	2 700	92	54 000	550	40	1253	50	12
68224	P20/S2/7W/40K/40/STD	7	E26	120	4 000	90	54 000	550	40	1 358	50	12
68225	P20/S2/7W/50K/25/STD	7	E26	120	5 000	90	54 000	550	25	2 350	50	12
68226	P20/S2/7W/50K/40/STD	7	E26	120	5 000	90	54 000	550	40	1 257	50	12
PAR30SN CCT SELECTABLE												
69643 ^{2,3}	P30S/11W/5CCT/25/STD	11	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	900	25	3 200	75	24
69644 ^{2,3}	P30S/11W/5CCT/40/STD	11	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	900	40	1 800	75	24
PAR30SN												
68227	P30S/S2/12W/27K/25/STD	12	E26	120	2 700	90	54 000	1 050	25	4 981	75	6
68228	P30S/S2/12W/27K/40/STD	12	E26	120	2 700	90	54 000	1 050	40	2 337	75	6
68229	P30S/S2/12W/30K/25/STD	12	E26	120	3 000	90	54 000	1 050	25	5 435	75	6
68230	P30S/S2/12W/30K/40/STD	12	E26	120	3 000	90	54 000	1 050	40	2 470	75	6
68233	P30S/S2/12W/50K/25/STD	12	E26	120	5 000	90	54 000	1 050	25	4 450	75	6

Lumen values are derived from photometric testing
For a complete list of compatible dimmers, please visit www.standardpro.com
¹ Not Energy Star

⁶₃
wet
location

⁶
damp
location


dimmable

²
3
yrs
warranty

²
5
yrs
warranty





PAR30LN
5 CCT



PAR38
5 CCT



PAR38
5 CCT



PAR30LN



PAR38

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Case qty (inner/master)
PAR30LN CCT SELECTABLE												
69645 ^{2,3}	P30L/11W/5CCT/25/STD	11	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	900	25	3 200	75	6/24
69646 ^{2,3}	P30L/11W/5CCT/40/STD	11	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	900	40	1 800	75	6/24
PAR30LN												
68235	P30L/S2/12W/27K/25/STD	12	E26	120	2 700	90	50 000	1 050	25	5 240	75	6
68236	P30L/S2/12W/27K/40/STD	12	E26	120	2 700	90	54 000	1 050	40	2 117	75	6
68239	P30L/S2/12W/40K/25/STD	12	E26	120	4 000	90	54 000	1 050	25	5 359	75	6
68241	P30L/S2/12W/50K/25/STD	12	E26	120	5 000	90	54 000	1 050	25	5 473	75	6
68242	P30L/S2/12W/50K/40/STD	12	E26	120	5 000	90	54 000	1 050	40	2 471	75	6
PAR38 CCT SELECTABLE												
69647 ^{2,3}	P38/14W/5CCT/25/STD	14	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	1 200	25	3 900	100	6/24
69648 ^{2,3}	P38/14W/5CCT/40/STD	14	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	1 200	40	2 500	100	6/24
69654 ^{2,3}	P38/14W/5CCT/25/BK/STD	14	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	1 200	25	3 900	100	6/24
69655 ^{2,3}	P38/14W/5CCT/40/BK/STD	14	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	1 200	40	2 500	100	6/24
PAR38												
68243	P38/S2/16.5W/27K/25/STD	16.5	E26	120	2 700	90	54 000	1 370	25	7 056	100	6
68245	P38/S2/16.5W/30K/25/STD	16.5	E26	120	3 000	90	50 000	1 370	25	7 354	120	6
68247	P38/S2/16.5W/40K/25/STD	16.5	E26	120	4 000	90	50 000	1 370	25	6 800	120	6
68250	P38/S2/16.5W/50K/25/STD	16.5	E26	120	5 000	90	54 000	1 370	25	6 800	120	6

Lumen values are derived from photometric testing
For a complete list of compatible dimmers, please visit www.standardpro.com
¹ Not Energy Star

⁶
wet
location


dimmable

²
3
yrs
warranty

²
5
yrs
warranty





PAR38 COLOR SELECTABLE LAMP

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Case qty (inner/master)
PAR38 Color Selectable												
69760	PAR38/8W/COLORSELECT/40/ND/STD	8	E26	120	6 color selectable-red,blue,green, yellow, orange, white (5 000K)	80	15 000	700	40	-	65	12

Lumen values are derived from photometric testing
For a complete list of compatible dimmers and ENERGY STAR qualified products,
please visit www.standardpro.com



non
dimable



wet
location



enclosed
fixture

