

# Lamp & Ballast kit

All the components to install an HID fixture are conveniently packed into a single box, ensuring that the installation can be completed all at once: lamp, capacitor (if required), ignitor (if required), mounting brackets, prewired ballast and hardware.



Order code	Description	Lamp watts (W)	ANSI code	Input volts (V)	Circuit type	Lamp shape	Lamp base	Lamp finish	Luminaire
<b>High Pressure Sodium</b>									
60995	LBK/BHPS0070/120/C/R/MED	70	S62	120	R-HPF	ED17	E26	Clear	Open
60996	LBK/BHPS0100/120/C/R/MED	100	S54	120	R-HPF	ED17	E26	Clear	Open
61010	LBK/BHPS0070/TRITAP/C/HX/MED	70	S62	120/277/347	HX-HPF	ED17	E26	Clear	Open
61012	LBK/BHPS0100/TRITAP/C/HX/MED	100	S54	120/277/347	HX-HPF	ED17	E26	Clear	Open
61013	LBK/BHPS0100/TRITAP/C/HX/MOG	100	S54	120/277/347	HX-HPF	ED23.5	E39	Clear	Open
61009	LBK/BHPS0150/120/C/R/MED	150	S55	120	R-HPF	ED17	E26	Clear	Open
61003	LBK/BHPS0150/TRITAP/C/HX/MOG	150	S55	120/277/347	HX-HPF	ED23.5	E39	Clear	Open
61004	LBK/BHPS0250/TRITAP/C/CWA/MOG	250	S50	120/277/347	CWA	ET18	E39	Clear	Open
61005	LBK/BHPS0400/TRITAP/C/CWA/MOG	400	S51	120/277/347	CWA	ET18	E39	Clear	Open

# Electronic Sign

Order code	Description	No. of lamps	Input volts	Max. case temp	Input power	Line current <sup>1</sup>	Open circuit volts	Min starting temp.	T8HO lamp footage (ft.)		T12HO lamp footage (ft.)	
			(V)	(°C)	(W)	(A)	(V)	(°C)	Min.	Max.	Min.	Max.
61015	ESB/12/216/UV/STD	1, 2	120 - 277	90	131	1.20	800	-29	4	12	2	16
61016	ESB/13/432/UV/STD	1, 2, 3	120 - 277	90	267	2.40	800	-29	4	24	4	32
61019	ESB/34/432/UV/STD	3, 4	120 - 277	90	267	2.40	800	-29	4	24	4	32
64172	ESB/14/1040/UV/STD	1, 2, 3, 4	120 - 277	90	352	3.00	1000	-29	8	32	10	40
61017	ESB/46/848/UV/STD	4, 5, 6	120 - 277	90	410	3.50	860	-29	16	36	8	48

# Electronic Transformer

Order code	Description	Input volts	Output volts	Input watts	Input current	Power factor	Auto reset	Dimmable	Min. starting temp.	Max. starting temp.	Dimensions
		(V)	(V)	(W)	(A)				(°C)	(°C)	L x W x H (mm)
61951 <sup>2</sup>	T120V/150W/AR/STD	120	11.4	150	1.27	0.99	Yes	Yes	-18	75	104 x 35 x 28

<sup>1</sup>Based off T12HO lamps at 120V

<sup>2</sup>Electronic halogen transformers are not designed to be compatible with LED MR16 replacement lamps. Using LED lamps with a halogen transformer may cause the lamps to flicker, strobe, or shut down.

