



CFL

CFL lamps provide the same amount of light (lumens) as regular incandescent lamps, but have a lower wattage rating. As a result, they consume less energy and cause less pollution. ALL STANDARD CFL lamps meet NEMA voluntary commitment on mercury content in CFL lamps and are all cULus listed, where applicable.

Specialty



20 W; MOL: 5 1/8 in. (130 mm)
Ø 2 9/32 in. (68 mm)

High Power
Factor



MOL: 6 1/16 in. (154 mm)
Ø 2 1/4 in. (57 mm)

Trilight

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
High Power Factor									
58404	CF20/HPF/27K/SPIRAL/E26/STD	20	E26	2 700	1 200	10 000	82	75	12/48
Trilight									
58959	CF13/20/25/27K/SPIRAL/E26/STD	13 20 25	E26	2 700	900 1 200 1 550	8 000	80	60 75 100	6/48



T2 Spiral



MOL : 3 13/16 in. (97 mm)

7 W



MOL : 3 31/32 in. (101 mm)

9 W



MOL : 4 1/8 in. (105 mm)

13 W



MOL : 4 11/32 in. (110 mm)

18 W



MOL : 4 7/8 in. (124 mm)

23 W



MOL : 5 1/16 in. (129 mm)

26 W

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
7 watts									
62764	CF7/T2/27K/SPIRAL/E26/ELUME	7	E26	2 700	430	10 000	82	40	6/48
9 watts									
61020	CF9/T2/27K/SPIRAL/E26/ELUME	9	E26	2 700	550	10 000	82	40	6/48
62311	CF9/T2/41K/SPIRAL/E26/ELUME	9	E26	4 100	550	10 000	82	40	6/48
13 watts									
61021	CF13/T2/27K/SPIRAL/E26/ELUME	13	E26	2 700	900	10 000	82	60	6/48
61024	CF13/T2/30K/SPIRAL/E26/ELUME	13	E26	3 000	900	10 000	82	60	6/48
61026	CF13/T2/35K/SPIRAL/E26/ELUME	13	E26	3 500	850	10 000	82	60	6/48
18 watts									
62832 ¹	CF18/T2/27K/SPIRAL/E26/STD	18	E26	2 700	1 250	12 000	82	75	6/48
62834 ¹	CF18/T2/35K/SPIRAL/E26/STD	18	E26	3 500	1 250	12 000	82	75	6/48
23 watts									
61032	CF23/T2/27K/SPIRAL/E26/ELUME	23	E26	2 700	1 600	10 000	82	100	6/48
61033	CF23/T2/30K/SPIRAL/E26/ELUME	23	E26	3 000	1 600	10 000	82	100	6/48
61034	CF23/T2/41K/SPIRAL/E26/ELUME	23	E26	4 100	1 600	10 000	82	100	6/48
61035	CF23/T2/50K/SPIRAL/E26/ELUME	23	E26	5 000	1 600	10 000	82	100	6/48
26 watts									
63389 ¹	CF26/T2/30K/SPIRAL/E26/STD	26	E26	3 000	1 750	10 000	82	100	6/48
T2 Spirals packs									
61022	CF13/T2/27K/SPIRAL/E26/ELUME 4P	13	E26	2 700	900	10 000	82	60	1/64
61025	CF13/T2/30K/SPIRAL/E26/ELUME 4P	13	E26	3 000	900	10 000	82	60	1/64
61027	CF13/T2/41K/SPIRAL/E26/ELUME 4P	13	E26	4 100	880	10 000	82	60	1/64
61023	CF13/T2/27K/SPIRAL/E26/ELUME 12P	13	E26	2 700	900	10 000	82	60	1/48

GU24 Based



13 W: MOL : 3 5/8 in. (92 mm)
Ø 1 13/16 in. (46 mm)
18 W: MOL : 4 13/32 in. (112 mm)
Ø 1 1/8 in. (54 mm)
23 W: MOL : 4 13/32 in. (112 mm)
Ø 1 1/8 in. (54 mm)

Spiral (GU24)



23 W: MOL : 4 27/32 in. (123 mm)
Ø 2 1/8 in. (54 mm)

Dimmable Spiral (GU24)

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
Spiral									
61843	CF13/T2/35K/SPIRAL/GU24/STD	13	GU24	3 500	880	10 000	82	60	6/48
61846	CF23/T2/27K/SPIRAL/GU24/STD	23	GU24	2 700	1 600	10 000	82	100	6/48
61847	CF23/T2/41K/SPIRAL/GU24/STD	23	GU24	4 100	1 600	10 000	82	100	6/48
Spiral - Dimmable									
60921 ¹	CF23/D/27K/SPIRAL/GU24/STD	23	GU24	2 700	1 500	10 000	82	100	6/48

High Wattage Spiral



MOL : 6 3/32 in. (155 mm)
Ø 2 5/8 in. (67 mm)

32 W



MOL : 7 9/32 in. (155 mm)
Ø 2 5/8 in. (67 mm)

40 W



MOL : 9 31/32 in. (253 mm)
Ø 4 1/32 in. (102 mm)

85 W

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
32 watts									
60932	CF32/27K/SPIRAL/E26/STD	32	E26	2 700	2 000	10 000	82	120	6/48
58412	CF32/65K/SPIRAL/E26/STD	32	E26	6 500	2 100	10 000	82	120	6/48
40 watts									
60940	CF40/35K/SPIRAL/E26/STD	40	E26	3 500	2 600	10 000	82	150	6/48
60942	CF40/50K/SPIRAL/E26/STD	40	E26	5 000	2 600	10 000	82	150	6/48
85 watts									
60926	CFL85/27K/SPIRAL/E26/STD	85	E26	2 700	5 400	10 000	82	350	6/12

