

Holiday

Order code	Description	Watts (W)	Base	Volts (V)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
C7.5								
MOL : 2 5/32 in. (55 mm) LCL : 1 1/2 in. (38 mm)								
52415	5C7.5/CW/1M/E12/120V/STD	5	E12	120	1 000	C-7A	Ceramic white	25/500
22002	5C7.5/CL/1M/E12/120V/STD	5	E12	120	1 000	C-7A	Clear	25/500
52179	5C7.5/TR/1M/E12/120V/STD	5	E12	120	1 000	C-7A	Transparent red	25/500
C9.25								
MOL : 2 7/8 in. (73 mm) LCL : 2 15/32 in. (63 mm)								
22003	7C9.25/CL/1M/E17/120V/STD	7	E17	120	1 000	C-7A	Clear	25/500
52187	7C9.25/TG/1M/E17/120V/STD	7	E17	120	1 000	C-7A	Transparent green	25/500
52189	7C9.25/TR/1M/E17/120V/STD	7	E17	120	1 000	C-7A	Transparent red	25/500

Colored

Order code	Description	Watts (W)	Base	Volts (V)	Average life (hrs)	Filament type	Finish/ Color	Case qty (inner/master)
A19 Ceramic								
MOL : 4 1/4 in. (108 mm) LCL : 2 27/32 in. (72 mm)								
52070	25A19/CB/5M/130V/STD	25	E26	130	5 000	C-9	Ceramic blue	6/24
52072	25A19/CP/5M/130V/STD	25	E26	130	5 000	C-9	Ceramic pink	6/24
52035	25A19/CY/5M/130V/STD	25	E26	130	5 000	C-9	Ceramic yellow	6/24
52078	40A19/CB/5M/130V/STD	40	E26	130	5 000	C-9	Ceramic blue	6/24
52094	100A19/CB/5M/130V/STD	100	E26	130	5 000	C-9	Ceramic blue	6/24

Order code	Description	Watts (W)	Base	Volts (V)	Average life (hrs)	Filament type	Finish/ Color	Case qty (inner/master)
------------	-------------	--------------	------	--------------	-----------------------	---------------	------------------	----------------------------

A19 Transparent

MOL : 4 1/4 in. (108 mm) LCL : 2 27/32 in. (72 mm)

52073	25A19/TA/5M/130V/STD	25	E26	130	5 000	C-9	Transparent amber	6/24
52077	25A19/TY/5M/130V/STD	25	E26	130	5 000	C-9	Transparent yellow	6/24
52039	60A19/TA/5M/130V/STD	60	E26	130	5 000	C-9	Transparent amber	6/24
52040	60A19/TB/5M/130V/STD	60	E26	130	5 000	C-9	Transparent blue	6/24

BR30 Transparent

MOL : 5 13/32 in. (137 mm) LCL : 3 3/8 in. (86 mm)

10083	75BR30/TA/5M/130V/STD	75	E26	130	5 000	C-9	Transparent amber	1/24
10081	75BR30/TB/5M/130V/STD	75	E26	130	5 000	C-9	Transparent blue	1/24

BR38

MOL : 5 25/32 in. (147 mm) LCL : 3 9/32 in. (83 mm)

50093	100BR38/A/5M/130V/STD	100	E26	130	5 000	C-9	Amber	1/12
50095	100BR38/G/5M/130V/STD	100	E26	130	5 000	C-9	Green	1/12
50098	100BR38/Y/5M/130V/STD	100	E26	130	5 000	C-9	Yellow	1/12

F10

MOL : 3 1/16 in. (78 mm) LCL : 1 21/32 in. (43 mm)

14456	15F10/A/2.5M/E12/130V	15	E12	130	2 500	C-7A	Amber	25/250
14460	25F10/A/2.5M/E12/130V	25	E12	130	2 500	CC-2V	Amber	25/250

F15

MOL : 4 1/4 in. (108 mm) LCL : 2 9/16 in. (65 mm)

50753	25F15/WH/1.5M/130V/STD	25	E26	130	1 500	CC-2V	White	25/100
50757	40F15/A/1.5M/130V/STD	40	E26	130	1 500	CC-2V	Amber	25/100
50754	40F15/WH/1.5M/130V/STD	40	E26	130	1 500	CC-2V	White	25/100
50758	60F15/A/1.5M/130V/STD	60	E26	130	1 500	CC-2V	Amber	25/100

Order code	Description	Watts (W)	Base	Volts (V)	Average life (hrs)	Filament type	Finish/ Color	Case qty (inner/master)
G11								
MOL : 2 5/16 in. (59 mm) LCL : 1 5/8 in. (41 mm)								
50764	7.5G11/CG/1M/130V/STD	7.5	E26	130	1 000	C-5	Ceramic green	25/500
50765	7.5G11/CO/1M/130V/STD	7.5	E26	130	1 000	C-5	Ceramic orange	25/500
50766	7.5G11/CR/1M/130V/STD	7.5	E26	130	1 000	C-5	Ceramic red	25/500
50767	7.5G11/CY/1M/130V/STD	7.5	E26	130	1 000	C-5	Ceramic Yellow	25/500
R20								
MOL : 3 31/32 in. (101 mm) LCL : 2 3/4 in. (70 mm)								
52060	50R20/A/5M/130V/STD	50	E26	130	5 000	C-9	Amber	6/24
52066	50R20/Y/5M/130V/STD	50	E26	130	5 000	C-9	Yellow	6/24
R20 Transparent								
MOL : 3 31/32 in. (101 mm) LCL : 2 3/4 in. (70 mm)								
52062	50R20/G/5M/130V/STD	50	E26	130	5 000	C-9	Green	6/24
52065	50R20/TP/5M/130V/STD	50	E26	130	5 000	C-9	Transparent pink	6/24
S11 Transparent								
MOL : 2 5/16 in. (59 mm) LCL : 1 5/8 in. (41 mm)								
50801	10S11/TR/1M/E17/130V/STD	10	E17	130	1 000	C-7A	Transparent red	25/500
S14 Ceramic								
MOL : 3 5/16 in. (84 mm) LCL : 2 17/32 in. (64 mm)								
52211	11S14/CB/3M/130V/STD	11	E26	130	3 000	C-9	Ceramic blue	25/500
52212	11S14/CG/3M/130V/STD	11	E26	130	3 000	C-9	Ceramic green	25/500
52214	11S14/CR/3M/130V/STD	11	E26	130	3 000	C-9	Ceramic red	25/500
22004	11S14/CY/3M/130V/STD	11	E26	130	3 000	C-9	Ceramic yellow	25/500
S14 Transparent								
MOL : 3 5/16 in. (84 mm) LCL : 2 17/32 in. (64 mm)								
52216	11S14/TA/3M/130V/STD	11	E26	130	3 000	C-9	Transparent amber	25/500
52217	11S14/TB/3M/130V/STD	11	E26	130	3 000	C-9	Transparent blue	25/500
52218	11S14/TG/3M/130V/STD	11	E26	130	3 000	C-9	Transparent green	25/500