

T8 - BALLAST BYPASS 3 & 5 CCT SELECTABLE

Standard's T8 - 3 & 5 CCT selectable are a great versatile retrofit solution. Available for ballast bypass installation, they cover a wide range of fixtures and applications. They are perfect to reduce inventory and maintenance!



4 ft - G13

8 ft - Fa8

Fa8 default (Switchable socket R17d included)

■ Color Selectable

A LED tube solution offering ultimate versatility, with the ability to change between 3 and 5 color temperatures for a variety of projects and applications. An ideal solution for reducing inventory.

■ Double-Ended Tube

Double-ended tubes are wired at both ends allowing them to work on shunted and non-shunted sockets. No socket rewiring is needed: simply bypass the ballast and insert the LED tube.

■ Easy Maintenance

They offer safe and simple installation which also allows for years of little to no maintenance with an extremely cost efficient operation.

Characteristics

- CCT switch
(3 000/3 500/4 000/5 000/6 500 K)

- All glass

- 220° beam angle

4FT - G13

- CCT switch
(4 000/5 000/6 500 K)

- All glass
PET Coating

- Includes 1 U-shape clip holder
for extra lamp support.

8FT - FA8

- Switchable socket G13 + FA8 & R17D
with the default socket Fa8.
Optional R17D base caps included.
DLC is only applicable to the Fa8 socket.



FA8 Cap



R17D Cap



Scan for more details

