

PROJECT: _____ DATE: _____

DISTRIBUTOR: _____ CATALOGUE #: _____ TYPE: _____

DRAWN BY: _____ CONTRACTOR: _____ PO: _____



SLIM PUCK 12 V LED UNDERCABINET LUMINAIRE

STANPRO

SPEC SHEET

FEATURES AND SPECIFICATIONS

CONSTRUCTION

Physical Characteristics

- Available finishes: brushed nickel, white and black
- Frosted lens
- Magnetic design, easily change the puck's finish using the compatible trims sold as accessory
- Slim profile of 0.27" (7 mm), allows for discreet surface mount application
- Wire gauge (AWG) : 22

Mounting

- Recessed and surface mount installation
- HUB required to connect pucks to the power supply
- Up to 15 pucks can be connected with a maximum of 5 pucks per HUB entry (see installation instructions for more details)


PERFORMANCE DATA

- Available in 3 000 K or 4 000 K single color temperatures
- 90+ CRI for true color accuracy
- Electrical ratings: 12 V
- Estimated life of over 50 000 hours to L70
- Dimming can be achieved using the compatible dimmer connectors (see accessories)
- Operating temperature : -20 °C to 40 °C (-4 °F to 104 °F)

COMPLIANCES

- cETLus listed for damp locations
- Meets requirements of ICES-005 class B for use in residential applications

TECHNICAL DRAWINGS



A	B	C	D	E
1/4" (0.7 cm)	Ø 3" (7.54 cm)	3 1/2" (9 cm)	31 7/8" (81 cm)	39 3/4" (101 cm)

* Please refer to the product web page to view detailed drawings by size.



QUICK SHIP AND TECHNICAL SPECIFICATION TABLE

Type	Order Code	Model Number	Watts (W)	Volts (VDC)	Color Temp. (K) ¹	Lumen Output per LED puck (lm) ²	Efficiency (lm/W)	CRI	Life L70 (hrs) ³	Beam Angle (°)	Finish	Lens Finish	Dimming (Yes/No)	Master Case QTY
Individual Puck														
	67168	UCP/12V/2.2W/30K/FR/WH/STD	2.2	12	3 000	150	68	90	50 000	120	White	Frosted	Yes	200
	67172	UCP/12V/2.2W/30K/FR/BLK/STD	2.2	12	3 000	150	68	90	50 000	120	Black	Frosted	Yes	200
	67174	UCP/12V/2.2W/40K/FR/BLK/STD	2.2	12	4 000	150	68	90	50 000	120	Black	Frosted	Yes	200
Kit of 3 Pucks														
	67171	UCP/KIT3/12V/2.2W/40K/FR/WH/STD	2.2	12	4 000	150	68	90	50 000	120	White	Frosted	Yes	30
	67173	UCP/KIT3/12V/2.2W/30K/FR/BLK/STD	2.2	12	3 000	150	68	90	50 000	120	Black	Frosted	Yes	30
	67177	UCP/KIT3/12V/2.2W/30K/FR/BN/STD	2.2	12	3 000	150	68	90	50 000	120	Brushed nickel	Frosted	Yes	30

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

³ Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.

ACCESSORIES*

Order Code	Model Number	Type	Figure	Case QTY (inner/master)
67180	UCP/TRIM/BACKPLATE/WH/STD	White trim and backplate	A	50 / 200
67181	UCP/TRIM/BACKPLATE/BLK/STD	Black trim and backplate	B	50 / 200
67182	UCP/TRIM/BACKPLATE/BN/STD	Brushed nickel trim and backplate	C	50 / 200
67183	UCP/ACC/HUB6/STD	HUB with 6 entries	D	30 / 120
67185 ¹	UCP/ACC/DIMMER/STD	ON/OFF and dimming switch	E	30 / 120
67186 ¹	UCP/ACC/MOTIONSENSOR/STD	Motion sensor and dimming switch	F	30 / 120

* Order separately.

¹ Dimming completed via connector and can be used with non dimmable drivers.



A



B



C



D



E



F



LED DRIVERS

Order Code	Model Number	Output Power (W)	Input Volts (VAC)	Input Current (mA)	Frequency (Hz)	IP Rating	Master Case QTY
Hardwired^{1,2} - Non-Dimmable							
65743	LED/DRIVER/10W/12V/HW/ND/STD	10	100-240	220	50/60	IP65	100
65744	LED/DRIVER/20W/12V/HW/ND/STD	20	100-240	250	50/60	IP65	100
Plug-in - Non-dimmable							
67184 ³	LED/DRIVER/12W/12V/PLUG/ND/STD	12	100-240	1 000	50/60	-	80
62265	LED/TAPE/36W/12V/WW+CW/PS/ND/STD	36	-	-	-	-	50

¹ Ensure hardwire connections are made in a junction box (junction box not included with driver).

² A wire to DC male connector (66241) is needed to allow hub connection to hardwire driver.

³ Included in the kit of 3 units.