

## Series Spec Sheet

# WHEELCHAIR SIGN

## STEEL SIGN FOR ACCESSIBILITY

In building sdesigned for accessibility, CSA B651 mandates the use of illuminated signage with accessibility symbols to guide individuals to safety. We answer this need by providing signs for areas of refuge, accessible elevator lobbies and paths to accessible exits.

### FEATURES AND SPECIFICATIONS

- **Circuitry - AC & AC/DC**
  - Nichia LED ultra bright light source
  - 120/277/347 V AC Input, field selectable
  - Emergency DC wattages as follows:  
**6 V DC = 0.9 W, 12 V DC = 0.9 W,  
 24 V DC = 0.9 W**
- **Circuitry - Self-powered**
  - Nichia LED ultra bright light source
  - 120/277/347 V AC Input, field selectable
  - High-performance, Ni-Cad battery
  - 120 minutes emergency duration
  - Solid state transfer and battery charger
- **Mechanical**
  - 20 gauge steel construction
  - Universal mounting: ceiling mount, wall mount, end mount
  - White powder coat finish
- **Approvals**
  - CSA Certified to C22.2 #141-15, C860
- **Compliance**
  - Meets requirements of ICES-005



### OVERVIEW

Light source	LED
Input voltage (V AC)	120/277/347
Input power	1.9 W AC & AC/DC (single or double face) 2W self-powered (single or double face)
DC voltage (V DC)	6, 12, 24
DC power (W)	0.9

### POWER CONSUMPTION TABLE

Model	Voltage	Power	Current
IB1	120 V	3.35 W	0.034 A
	277 V	2.63 W	0.01 A
	347 V	3.31 W	0.012 A
UDC	120 V	1.8 W	0.022 A
	277 V	1.4 W	0.006 A
	347 V	1.7 W	0.007 A



luminaire  
DEL



NMB  
005




Energy-Verified  
Energie-Vérifiée

ORDERING GUIDE

RMS				
Series	Nbr of faces	Color	DC Volts (V DC)	Options
RMS	1 - Single face 2 - Double face	WH - White	UDC - Universal DC backup voltage IB1 - from 6 to 24V Self-powered for 120 minutes	RL - Refuge Left RR - Refuge Right EL - Elevator Left ER - Elevator Right

DIMENSIONS



CONFIGURATIONS



Elevator signage



Refuge signage

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.  
All products are subject to change or may be discontinued any time without notice.