

High Pressure Sodium



MOL.: 11 1/2 in. (292 mm)
Ø 4 5/8 in. (117.5 mm)
LCL.: 7 in. (178 mm)

ED23.5



MOL.: 11 1/2 in. (292 mm)
Ø 4 5/8 in. (117.5 mm)
LCL.: 7 in. (178 mm)

ED17



MOL.: 11 1/2 in. (292 mm)
Ø 4 5/8 in. (117.5 mm)
LCL.: 7 in. (178 mm)

ET18



MOL.: 11 1/2 in. (292 mm)
Ø 4 5/8 in. (117.5 mm)
LCL.: 7 in. (178 mm)

E25

Order code	Description	Shape	Base	ANSI code	Color temp. (K)	Lumen output (lm)	Mean lumens (lm)	Average life (hrs)	CRI	Operating position	Finish	Luminaire	Case qty (master)
35 watts													
70157	LU35/MED STD	ED17	E26	S76/E	1 900	2 250	2 050	16 000	22	U	Clear	E	12
50 watts													
70160	LU50/MED STD	ED17	E26	S68/E	1 900	4 000	3 600	24 000	22	U	Clear	E	12
70159	LU50/ECO STD	ED23.5	E39	S68/E	1 900	4 000	3 600	24 000	22	U	Clear	E	12
70 watts													
70162	LU70/MED STD	ED17	E26	S62/E	1 900	6 300	5 350	24 000	22	U	Clear	E	12
70161	LU70/ECO STD	ED23.5	E39	S62/E	1 900	6 300	5 500	24 000	22	U	Clear	E	12
100 watts													
70152	LU100/MED STD	ED17	E26	S54/E	1 900	9 500	8 000	24 000	22	U	Clear	E	12
70151	LU100/ECO STD	ED23.5	E39	S54/E	1 900	9 500	8 550	24 000	22	U	Clear	E	12
150 watts													
70155	LU150/MED STD	ED17	E26	S55/E	2 000	15 000	13 800	24 000	20	U	Clear	E	12
70154	LU150/55/ECO STD	ED23.5	E39	S55/E	1 900	16 000	13 800	24 000	22	U	Clear	E	12
250 watts													
70156	LU250/ECO STD	ET18	E39	S50/E	1 900	28 000	26 100	24 000	22	U	Clear	E	12
400 watts													
70158	LU400/ECO STD	ET18	E39	S51/E	1 900	50 000	45 000	24 000	22	U	Clear	E	12
1000 watts													
70153	LU1000/ECO STD	E25	E39	S52/E	2 000	140 000	126 000	24 000	30	U	Clear	E	12

E = Enclosed rated for indoor or outdoor fixtures