

# Safety Max™ Lamps



Incandescent Lamps

With STANDARD Safety Max™, you protect the products of the production line, without sacrificing lumen output. Should a Safety Max™ lamp break, virtually all glass, mercury, metal and phosphors are contained by the safety coating. Disposal and lamp changes are also easy and safe.

Therefore, you can prevent contamination, minimize risk and avoid your business being shut down.

| Order code | Description                      | Watts<br>(W) | Base  | Volts<br>(V) | Lumens at 120 V<br>(lm) | Average life<br>(hrs) | Filament type | Coating  | Finish | MOL<br>(in.) (mm) |      | LCL<br>(in.) (mm) |     | Case qty<br>(inner/master) |
|------------|----------------------------------|--------------|-------|--------------|-------------------------|-----------------------|---------------|----------|--------|-------------------|------|-------------------|-----|----------------------------|
| A15        |                                  |              |       |              |                         |                       |               |          |        |                   |      |                   |     |                            |
| 46063      | 25A15/F/5M/130V/STD SM           | 25           | E26   | 130          | 150                     | 5 000                 | C-9           | Mylon    | Frost  | 3.5               | 89.0 | 2.4               | 60  | 6/60                       |
| 67723      | 40A15/F/5M/130V/HIGH TEMP/STD SM | 40           | E26   | 130          | 320                     | 5 000                 | C-9           | PFA      | Frost  | 3.4               | 86.0 | 2.4               | 62  | 6/60                       |
| 67724      | 40A15/F/5M/130V/LOW TEMP/STD SM  | 40           | E26   | 130          | 320                     | 5 000                 | C-9           | Silicone | Frost  | 3.4               | 86.0 | 2.4               | 62  | 6/60                       |
| 69671      | 40A15/F/6.5M/250V SM             | 40           | E26   | 250          | 300                     | 6 500                 | C-9           | PFA      | Frost  | 3.5               | 89.0 | 2.4               | 60  | 1/100                      |
| A19        |                                  |              |       |              |                         |                       |               |          |        |                   |      |                   |     |                            |
| 10123      | 25A19/F/6M/130V/STD SM           | 25           | E26   | 130          | 168                     | 6 000                 | C-9           | Silicone | Frost  | 4.2               | 108  | 2.9               | 73  | 24/120                     |
| 51092      | 60A19/F/6M/130V/STD SM           | 60           | E26   | 130          | 410                     | 6 000                 | C-9           | Silicone | Frost  | 4.2               | 108  | 3.1               | 79  | 6/24                       |
| 10131      | 60A19/F/RS/130V/STD SM           | 60           | E26   | 130          | 350                     | 5 000                 | C-9           | Silicone | Frost  | 4.2               | 108  | 3.1               | 79  | 6/24                       |
| 10129      | 75A19/F/RS/130V/STD SM           | 75           | E26   | 130          | 540                     | 5 000                 | C-9           | Silicone | Frost  | 4.2               | 108  | 3.1               | 79  | 6/24                       |
| 69173      | 100A19/F/RS/130V/STD/2P SM       | 100          | E26   | 130          | 780                     | 5 000                 | C-9           | Mylon    | Frost  | 4.2               | 108  | 3.1               | 79  | 12/120                     |
| A21        |                                  |              |       |              |                         |                       |               |          |        |                   |      |                   |     |                            |
| 10372      | 100A21/F/5M/130V/STD SM          | 100          | E26   | 130          | 1 030                   | 5 000                 | C-9           | Silicone | Frost  | 5.3               | 135  | 3.5               | 90  | 6/24                       |
| A23        |                                  |              |       |              |                         |                       |               |          |        |                   |      |                   |     |                            |
| 50912      | 200A23/F/5M/130V/STD SM          | 200          | E26   | 130          | 1 640                   | 5 000                 | C-9           | Silicone | Frost  | 6.2               | 157  | 5.1               | 128 | 20/60                      |
| 10125      | 200A23/F/RS/130V/STD SM          | 200          | E26   | 130          | 2 335                   | 5 000                 | C-9           | Silicone | Frost  | 6.3               | 160  | 4.6               | 117 | 6/24                       |
| B10        |                                  |              |       |              |                         |                       |               |          |        |                   |      |                   |     |                            |
| 10119      | 60B10/CL/3M/130V/STD SM          | 60           | E26   | 130          | 550                     | 3 000                 | C-9           | Silicone | Clear  | 3.9               | 99   | 2.1               | 53  | 6/24                       |
| BR40       |                                  |              |       |              |                         |                       |               |          |        |                   |      |                   |     |                            |
| 69675      | 250BR40/IR/CL/6M/120V SM         | 250          | E26   | 120          | 2 400                   | 6 000                 | C-9           | PFA      | Clear  | 6.5               | 165  | 4.3               | 108 | 1/12                       |
| PS25       |                                  |              |       |              |                         |                       |               |          |        |                   |      |                   |     |                            |
| 10254      | 150PS25/F/RS/130V/STD SM         | 150          | E26   | 130          | 1 120                   | 3 000                 | C-9           | Silicone | Frost  | 6.9               | 176  | 5.3               | 133 | 20/60                      |
| 10255      | 200PS25/F/RS/130V/STD SM         | 200          | E26   | 130          | 1 640                   | 3 000                 | C-9           | Silicone | Frost  | 6.9               | 176  | 5.3               | 133 | 6/24                       |
| 10126      | 300PS25/F/5M/130V/STD SM         | 300          | E26   | 130          | 2 460                   | 5 000                 | C-9           | Silicone | Frost  | 6.9               | 176  | 5.3               | 133 | 6/24                       |
| R12 - R40  |                                  |              |       |              |                         |                       |               |          |        |                   |      |                   |     |                            |
| 11813      | 20R12/CL/13V/ BA15S/SM           | 20           | BA15s | 13           | N/A                     | 300                   | C-8           | Mylon    | Clear  | 2.6               | 66   | N/A               | N/A | 10/50                      |
| 69673      | 250R40/IR/R/6M/120 130V/STD SM   | 250          | E26   | 120          | N/A                     | 6 000                 | C-9           | PFA      | Red    | 6.6               | 167  | 3.9               | 99  | 1/12                       |
| 69674      | 375R40/IR/CL/6M/120V SM          | 375          | E26   | 120          | N/A                     | 6 000                 | C-9           | PFA      | Clear  | 7.6               | 193  | 4.2               | 106 | 1/12                       |