



# A & PS High Intensity



A21 18 W 120 V



A21 20 W 120-277 V



PS30 36W 120-277 V

| Order code            | Description                   | Watts (W) | Base | Volts (VAC) | Color temp. (K) | CRI | Beam angle (°) | Life L70 (hrs) | Lumen output (lm) | Case qty (master) |
|-----------------------|-------------------------------|-----------|------|-------------|-----------------|-----|----------------|----------------|-------------------|-------------------|
| <b>A21 120 V</b>      |                               |           |      |             |                 |     |                |                |                   |                   |
| 68920                 | A21HO/18W/30K/120/STD         | 18        | E26  | 120         | 3 000           | 90  | 220            | 25 000         | 2 000             | 12                |
| 68921                 | A21HO/18W/40K/120/STD         | 18        | E26  | 120         | 4 000           | 90  | 220            | 25 000         | 2 000             | 12                |
| 68922                 | A21HO/18W/50K/120/STD         | 18        | E26  | 120         | 5 000           | 90  | 220            | 25 000         | 2 000             | 12                |
| <b>A21 120-277 V</b>  |                               |           |      |             |                 |     |                |                |                   |                   |
| 69003                 | A21HO/20W/30K/120-277/ND/STD  | 20        | E26  | 120-277     | 3 000           | 80  | 260            | 25 000         | 2 600             | 12                |
| 69004                 | A21HO/20W/40K/120-277/ND/STD  | 20        | E26  | 120-277     | 4 000           | 80  | 260            | 25 000         | 2 600             | 12                |
| 69005                 | A21HO/20W/50K/120-277/ND/STD  | 20        | E26  | 120-277     | 5 000           | 80  | 260            | 25 000         | 2 600             | 12                |
| <b>PS30 120-277 V</b> |                               |           |      |             |                 |     |                |                |                   |                   |
| 68926 <sup>1</sup>    | PS30/36W/40K/120-277/EX39/STD | 36        | EX39 | 120-277     | 4 000           | 80  | 270            | 50 000         | 4 500             | 6                 |
| 68927 <sup>1</sup>    | PS30/36W/50K/120-277/EX39/STD | 36        | EX39 | 120-277     | 5 000           | 80  | 270            | 50 000         | 4 500             | 6                 |

## Traditional Equivalent

| LED  | CFL         | Incandescent | HID         |
|------|-------------|--------------|-------------|
| 18 W | 32 W        | 150 W        | 50 W        |
| 20 W | 32 W - 40 W | 150 W - 200W | 50 W - 75 W |
| 36 W | 55 W        | 300 W        | 100 W       |

Lumen values are derived from photometric testing. For a complete list of compatible ballasts and DLC qualified products, please visit [www.standardpro.com](http://www.standardpro.com)

