



# LED General Purpose

Combining a comfortable, pleasing atmosphere with energy efficiency is now possible with STANDARD's smooth dimming LED lamps. Choose from our large selection of lamp shapes and create your own style while saving on energy and maintenance costs.

From Omni lamps to small halogen replacements, these lamps deliver a brighter look and provide the same even, crisp and comfortable lighting as traditional lamps. A wide selection of color temperatures is offered to obtain the desired lighting effect and can be adapted to all applications.



A19 6W S6



A19 8W S6



A19 13W S6



A19 S5



A19 4 pack



A19 GU24



A19 15W

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	Finish	CRI	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Dimming capability (Yes/No)	Case qty (inner/master)
<b>A19 40 W equivalent</b>												
69676	A19/S6/6W/27K/STD	6	E26	120	2 700	Frost	80	25 000	480	40	Yes	1/50
67949	LED/A19/S5/6W/30K/STD	6	E26	120	3 000	Frost	80	25 000	480	40	Yes	1/100
69678	A19/S6/6W/40K/STD	6	E26	120	4 000	Frost	80	25 000	480	40	Yes	1/50
67951	LED/A19/S5/6W/50K/STD	6	E26	120	5 000	Frost	80	25 000	480	40	Yes	1/100
<b>60 W equivalent</b>												
67952	LED/A19/S5/9W/27K/STD	9	E26	120	2 700	Frost	80	25 000	800	60	Yes	1/100
69681	A19/S6/8W/30K/STD	8	E26	120	3 000	Frost	80	25 000	800	60	Yes	1/50
67954	LED/A19/S5/9W/40K/STD	9	E26	120	4 000	Frost	80	25 000	800	60	Yes	1/100
67955	LED/A19/S5/9W/50K/STD	9	E26	120	5 000	Frost	80	25 000	800	60	Yes	1/100
<b>60 W equivalent - 4 pack</b>												
68001	LED/A19/S2/9W/27K/STD 4P	9	E26	120	2 700	Frost	80	25 000	800	60	Yes	1/96
68002	LED/A19/S2/9W/30K/STD 4P	9	E26	120	3 000	Frost	80	25 000	800	60	Yes	1/96
68003	LED/A19/S2/9W/40K/STD 4P	9	E26	120	4 000	Frost	80	25 000	800	60	Yes	1/96
69695	A19/S6/8W/50K/STD 4P	8	E26	120	5 000	Frost	80	25 000	800	60	Yes	1/48
<b>60 W equivalent - GU24</b>												
66275	A19/9.8W/27K/GU24/PRO/STD	9.8	GU24	120	2 700	Frost	83	25 000	814	60	Yes	6/48
66276	A19/9.8W/30K/GU24/PRO/STD	9.8	GU24	120	3 000	Frost	82	25 000	887	60	Yes	6/48
66277	A19/9.8W/40K/GU24/PRO/STD	9.8	GU24	120	4 000	Frost	86	25 000	868	60	Yes	6/48
<b>75 W equivalent</b>												
67956	LED/A19/S5/12W/27K/STD	12	E26	120	2 700	Frost	80	25 000	1 100	75	Yes	1/100
67957	LED/A19/S5/12W/30K/STD	12	E26	120	3 000	Frost	80	25 000	1 100	75	Yes	1/100
67958	LED/A19/S5/12W/40K/STD	12	E26	120	4 000	Frost	80	25 000	1 100	75	Yes	1/100
67959	LED/A19/S5/12W/50K/STD	12	E26	120	5 000	Frost	80	25 000	1 100	75	Yes	1/100
<b>100 W equivalent</b>												
69688	A19/S6/13W/27K/STD	13	E26	125	2 700	Frost	80	25 000	1600	100	Yes	1/50
69689	A19/S6/13W/30K/STD	13	E26	125	3 000	Frost	80	25 000	1600	100	Yes	1/50
69690	A19/S6/13W/40K/STD	13	E26	125	4 000	Frost	80	25 000	1600	100	Yes	1/50
66191	ED/A19/S4/15W/50K/STD	15	E26	120	5 000	Frost	85	25 000	1 725	100	Yes	6/48

Lumen values are derived from photometric testing  
 For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit [www.standardpro.com](http://www.standardpro.com)





Trilight

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	Finish	CRI	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Dimming capability (Yes/No)	Case qty (inner/master)
<b>Trilight</b>												
65613	LED/A19/S2/12W/27K/3WAY/STD	3/9/12	E26	120	2 700	Frost	81	25 000	280/950/1 200	30/70/100	No	6/24
65614	LED/A19/S2/12W/30K/3WAY/STD	3/9/12	E26	120	3 000	Frost	83	25 000	280/950/1 200	30/70/100	No	6/24

Lumen values are derived from photometric testing  
 For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit [www.standardpro.com](http://www.standardpro.com)



Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	Finish	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Case qty (inner/master)
<b>A15</b>										
66758	A15/S2/6W/27K/CL/STD	6	E26	120	2 700	Clear	15 000	514	60	24/48
66759	A15/S2/5.5W/27K/FR/STD	5.5	E26	120	2 700	Frost	15 000	496	60	24/48
66760	A15/S2/6W/30K/CL/STD	6	E26	120	3 000	Clear	15 000	592	60	24/48
66761	A15/S2/5.5W/30K/FR/STD	5.5	E26	120	3 000	Frost	15 000	511	60	24/48
66762	A15/S2/5.5W/40K/FR/STD	5.5	E26	120	4 000	Frost	15 000	530	60	24/48
<b>C12</b>										
66763	C12/S2/4.5W/27K/CL/STD	4.5	E26	120	2 700	Clear	15 000	322	40	24/48
66764	C12/S2/4.5W/27K/E12/CL/STD	4.5	E12	120	2 700	Clear	15 000	322	60	24/48
66765	C12/S2/4.5W/27K/E12/FR/STD	4.5	E12	120	2 700	Frost	15 000	331	60	24/48
<b>G16.5</b>										
66766	G16.5/S2/5W/27K/E12/CL/STD	5	E12	120	2 700	Clear	15 000	365	60	24/48
66767	G16.5/S2/5W/27K/E12/FR/STD	5	E12	120	2 700	Frost	15 000	361	60	24/48
<b>G25</b>										
66768	G25/S2/7W/27K/FR/STD	7	E26	120	2 700	Frost	15 000	553	60	24/48
66769	G25/S2/7W/30K/FR/STD	7	E26	120	3 000	Frost	15 000	553	60	24/48

Lumen values are derived from photometric testing  
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit [www.standardpro.com](http://www.standardpro.com)

