

Neodymium



MOL: 1 13/16 in. (46 mm)
Ø 2 in. (51 mm)

MR16 (GU5.3)



MOL: 3 21/32 in. (46 mm)
Ø 3 3/4 in. (95 mm)

PAR30

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (inner/master)
MR16											
60871	H50MR16/FL/N/CG/2M/GU5.3/12V/STD	50	GU5.3	12	550	2 000	Neo.	38	Flood	1 400	12/120
PAR30											
58360 ²	H75PAR30/FL/N/2M/130V/STD	75	E26	130	1 000	2 000	Neo.	30	Flood	N/A	1/15

ICE



MOL: 2 5/32 in. (45 mm)
Ø 2 in. (51 mm)

ES16 (GU10)



MOL: 1 25/32 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GX5.3)



MOL: 4 13/16 in. (95 mm)
Ø 3 3/4 in. (95 mm)

PAR30LN

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (inner/master)
ES16										
55051 ¹	H35GU10/CG/2.5M/120V/STD ICE	35	GU10	120	280	2 500	40	Flood	600	10/200
55038 ¹	H50GU10/CG/2.5M/120V/STD ICE	50	GU10	120	500	2 500	40	Flood	840	10/200
55037 ¹	H50GU10/CG/2.5M/130V/STD ICE	50	GU10	130	375	2 500	40	Flood	840	10/200
MR16										
55039	H50MR16/5M/GX5.3/12V/STD ICE	50	GX5.3	12	850	5 000	N/A	Flood	N/A	10/200
PAR30LN										
50189 ²	H50PAR30/LN/FL/2.5M/120V/STD ICE	50	E26	120	600	2 500	N/A	Flood	N/A	1/15
50188 ²	H50PAR30/LN/FL/5M/130V/STD ICE	50	E26	130	450	5 000	N/A	Flood	N/A	1/15

¹ This product is affected by provincial Energy Efficiency Regulations in British Columbia. Note that it will remain available until stock is depleted.
² This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.

UNI-FROST™



MOL: 1.25/32 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GX5.3)




MOL: 2.5/32 in. (45 mm)
Ø 2 in. (51 mm)

ES16 (GU10)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Colour/Finish	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (inner/master)
MR16 - Cover Glass											
57211 ¹	H50MR16/CG/4M/GU5.3/12V/STD UFR	50	GU5.3	12	750	4 000	Frost	N/A	N/A	N/A	10/200
ES16 - Cover Glass											
57212 ^{1,2}	H35GU10/CG/2.5M/120V/STD UFR	35	GU10	120	330	2 500	Frost	N/A	N/A	N/A	10/200
57213 ^{1,2}	H50GU10/CG/2.5M/120V/STD UFR	50	GU10	120	520	2 500	Frost	N/A	N/A	N/A	10/200
57801 ^{1,2}	H50GU10/CG/3M/130V/STD UFR	50	GU10	130	390	3 000	Frost	N/A	N/A	N/A	10/200

Colored



MOL: 1.25/32 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GX5.3)



MOL: 3.9/32 in. (83 mm)
Ø 2.5 in. (63.5 mm)

PAR20



MOL: 3.21/32 in. (83 mm)
Ø 3.3/4 in. (85 mm)

PAR30



MOL: 5.5/16 in. (135 mm)
Ø 4.3/4 in. (121 mm)

PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Average life (hrs)	Color	Beam angle (°)	Beam spread	Case qty (inner/master)
MR16									
55064	H50MR16/FL/G/CG/4M/GX5.3/12V/STD	50	GX5.3	12	4 000	Green	38	Flood	10/200
55066	H50MR16/FL/R/CG/4M/GX5.3/12V/STD	50	GX5.3	12	4 000	Red	38	Flood	10/200
55067	H50MR16/FL/Y/CG/4M/GX5.3/12V/STD	50	GX5.3	12	4 000	Yellow	38	Flood	10/200
PAR20									
55002	H35PAR20/NFL/G/2M/130V/STD	35	E26	130	2 000	Green	30	Narrow Flood	1/15
55004	H35PAR20/NFL/B/2M/130V/STD	35	E26	130	2 000	Blue	30	Narrow Flood	1/15
PAR30									
55006	H50PAR30/FL/R/2M/130V/STD	50	E26	130	2 000	Red	30	Flood	1/15
55007	H50PAR30/FL/G/2M/130V/STD	50	E26	130	2 000	Green	30	Flood	1/15
55008	H50PAR30/FL/Y/2M/130V/STD	50	E26	130	2 000	Yellow	30	Flood	1/15
PAR38									
51182	H90PAR38/FL/G/2M/MS/130V/STD	90	E26	130	2 000	Green	30	Flood	1/15
51183	H90PAR38/FL/R/2M/MS/130V/STD	90	E26	130	2 000	Red	30	Flood	1/15
51184	H90PAR38/FL/Y/2M/MS/130V/STD	90	E26	130	2 000	Yellow	30	Flood	1/15

¹This product is affected by provincial Energy Efficiency Regulations in British Columbia. Note that it will remain available until stock is depleted.

MR11 & MR16



MOL: 1.378 in. (35 mm)
Ø 1.376 in. (35 mm)

MR11 (G4)



MOL: 1.25/32 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GX5.3)



MOL: 2.5/32 in. (65 mm)
Ø 2 in. (51 mm)

MR16 (E26)



MOL: 1.25/32 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GU10)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Beam angle (°)	Beam spread	Case qty (inner/master)
MR11 - Cover Glass										
55054	H5MR11/NSP/CG/2M/G4/12V/STD	5	G4	12	45	2 000	2 900	10	Narrow Spot	12/120
50899	H35MR11/MFL/CG/2M/G4/12V/FTH STD	35	G4	12	345	2 000	2 900	28	Flood	10/200
MR11 - Open										
50894	H20MR11/NSP/AX/G4/12V/FTB STD	20	G4	12	200	2 000	2 900	11	Narrow Spot	12/120
50898	H35MR11/MFL/AX/G4/12V/FTH STD	35	G4	12	345	2 000	2 900	30	Flood	12/120
MR16 - Cover Glass										
51134 ¹	H20MR16/FL/CG/4M/GX5.3/12V/BAB STD	20	GX5.3	12	260	4 000	2 950	38	Flood	10/200
50892 ¹	H35MR16/FL/CG/4M/GX5.3/12V/FMW STD	35	GX5.3	12	530	4 000	3 000	38	Flood	10/200
50893	H50MR16/FL/CG/4M/GX5.3/12V/EXN STD	50	GX5.3	12	850	4 000	3 050	38	Flood	10/200
MR16 - Cover Glass - Line Voltage										
55570 ^{1,2}	H35MR16/FL/CG/2M/E26/120V/STD	35	E26	120	240	2 000	2 800	38	Flood	10/200
55569 ^{1,2}	H50MR16/FL/CG/2M/E26/120V/STD	50	E26	120	420	2 000	2 800	38	Flood	10/200
59590 ^{1,2}	H35MR16/FL/CG/E26/130V/STD	35	E26	130	180	2 500	2 800	38	Flood	10/200
59589 ^{1,2}	H50MR16/FL/CG/E26/130V/STD	50	E26	130	315	2 500	2 800	38	Flood	10/200
MR16 (GU10)										
55034 ¹	H20GU10/NFL/CG/2.5M/120V/STD	20	GU10	120	120	2 500	2 800	25	Narrow Flood	10/200
55033 ¹	H35GU10/NFL/CG/2.5M/120V/STD	35	GU10	120	280	2 500	2 800	25	Narrow Flood	10/200
10437 ¹	H50GU10/NFL/CG/2.5M/120V/STD	50	GU10	120	375	2 500	2 800	25	Narrow Flood	10/200
55035	H50GU10/NFL/2M/CG/120V/ HS	50	GU10	120	N/A	2 000	2 800	25	Narrow Flood	10/200
10438 ¹	H50GU10/NFL/CG/3M/130V/STD	50	GU10	130	500	3 000	2 800	25	Narrow Flood	10/200
MR16 - Open										
51066 ¹	H20MR16/FL/4M/GX5.3/12V/BAB STD	20	GX5.3	12	260	4 000	2 950	36	Flood	10/200
50888 ¹	H35MR16/FL/4M/GX5.3/12V/FMW STD	35	GX5.3	12	530	4 000	3 000	38	Flood	10/200
50890	H50MR16/NFL/4M/GX5.3/12V/EXZ STD	50	GX5.3	12	850	4 000	3 050	24	Narrow Flood	10/200
50891	H50MR16/FL/4M/GX5.3/12V/EXN STD	50	GX5.3	12	850	4 000	3 050	38	Flood	10/200

¹This product is affected by provincial Energy Efficiency Regulations in British Columbia. Note that it will remain available until stock is depleted.