

Safety Max™

With STANDARD Safety Max™, you protect the products of the production line, without sacrificing lumen output.

Should a Safety Max™ lamp break, virtually all glass, mercury, metal and phosphors are contained by the safety coating. Disposal and lamp changes are also easy and safe. Therefore, you can prevent contamination, minimize risk and avoid your business being shut down.



Order code	Description	Watts (W)	Base	ANSI code	Color temp. (K)	Lumen output (lm)	Mean Lumens (lm)	Average life (hrs)	CRI	Shape	Coating	Operating position	Finish	Case qty (inner/master)
Metal Halide														
68721	MP50W/U/UVS/PS STD SM	50	E26	M110/O	4 200	3 200	2 100	10 000	65	EDX17	PTFE	U	Clear	1/12
68624	MH175W/U STD SM	175	E39	M57/E	4 000	14 000	9 100	10 000	65	ED28	PTFE	U	Clear	1/12
68628	MH175W/U/MED STD SM	175	E26	M57/E	4 000	14 000	9 100	10 000	65	ED17	PTFE	U	Clear	1/12
68626	MH250W/U STD SM	250	E39	M58/E	4 200	21 000	13 700	10 000	65	ED28	PTFE	U	Clear	1/12
68623	MH400W/U STD SM	400	E39	M59/E	4 000	36 000	23 000	20 000	65	ED37	PTFE	U	Clear	1/6
68627	MPI400W/BU STD SM	400	EX39	M59/O	4 000	38 000	30 400	20 000	65	ED37	PTFE	U	Clear	1/6
High Pressure Sodium														
11207	LU70/MED EYE SM	70	E26	S62	1 900	6 300	5 350	24 000	22	ED17	PTFE	U	Clear	1/12
11706	LU150/55 EYE SM	150	E39	S55	1 900	24 000	16 000	1 900	22	ED23.5	PTFE	U	Clear	1/12
11205	LU250 EYE SM	250	E39	S50	1 900	24 000	28 500	1 900	22	ET18	PTFE	U	Clear	1/12
11206	LU400 EYE SM	400	E39	S51	1 900	24 000	50 000	1 900	22	ET18	PTFE	U	Clear	1/12