

Réflecteur



MOL : 3 3/4 in. (95 mm)
Ø 2 15/32 in. (63 mm)

PAR20



MOL : 4 7/8 in. (124 mm)
Ø 2 7/16 in. (62 mm)

R20

Code de commande	Description	Watts (W)	Culot	Couleur temp. (K)	Flux lumineux (lm)	Vie moyenne (h)	IRC	Équivalent incandescente (W)	Qté caisse (int./ext.)
PAR20									
14100 ¹	CF9/27K/PAR20/E26/STD	9	E26	2 700	300	8 000	82	50	6/48
14102 ¹	CF9/35K/PAR20/E26/STD	9	E26	3 500	300	8 000	82	50	6/48
R20									
14162	CF11/27K/R20/E26/STD	11	E26	2 700	350	8 000	82	50	6/48

Cathode froide



MOL : 4 17/32 in. (115 mm)
Ø 2 3/8 in. (60 mm)

A19

Code de commande	Description	Watts (W)	Culot	Couleur temp. (K)	Flux lumineux (lm)	Vie moyenne (h)	Couleur	IRC	Équivalent incandescente (W)	Qté caisse (int./ext.)
A19										
58427	CCFL8/F/A19/25M/E26/STD	8	E26	2 700	320	25 000	Givrée	82	35-40	1/48



¹ Convient aux emplacement extérieur (culot vers le haut)