



DEL Filament Haute Intensité



Code de commande	Description	Watts (W)	Culot	Volts (VCA)	Temp. de couleur (K)	IRC	Faisceau (°)	Vie L70 (h)	Flux lumineux (lm)	Qté caisse (int./ext.)
70174	ED23.5/20W/30K/BYP/E26/V/FIL/ND/STD	20	E26	120-277	3 000	80	Universal	25 000	3 500	12
70175	ED23.5/20W/40K/BYP/E26/V/FIL/ND/STD	20	E26	120-277	4 000	80	Universal	25 000	3 500	12
69598	ED23.5/20W/40K/BYP/EX39/V/FIL/ND/STD	20	EX39	120-277	4 000	80	Universal	25 000	3 500	12
69599	ED28/40W/40K/BYP/EX39/V/FIL/ND/STD	40	EX39	120-277	4 000	80	Universal	25 000	7 500	12
69600	ED37/65W/40K/BYP/EX39/V/FIL/ND/STD	65	EX39	120-277	4 000	80	Universal	25 000	12 000	6

Équivalent traditionnel

DEL	LFC	Incandescente	DHI
20 W	40 W - 45 W	150 W - 200 W	70 W - 100 W
40 W	85 W - 105 W	500 W	150 W - 200 W
65 W	-	-	400 W

Les valeurs de lumen proviennent des essais photométriques

66
endroits
mouillés

luminaire
fermé

sans
gradation

3 ans
garantie

ETL
Intertek