

EMERGENCY LIGHTING

Options

For the list of options available to a specific series, please consult its catalogue page

Option	Description
ACTB	AC Terminal Block
A	Ammeter
AT	Automatic test Self-diagnostic
AT/AUD	Audible Alarm
BO	Black Out Option
WO	White Out Option
BD	Battery Disconnect
CT	Remote Load Cab tire Set
CCWH	White end caps & canopy kit (RMEA only)
CPS	Constant Power Supply
DCTB	DC Terminal Block
DL	Damp Location Rated
FA	Fire Alarm Flasher
FLA	Flasher and Audible Alarm
FL	Flasher (specify Voltage)
FD2	2 Circuit Fused Internal Distribution
FD3	3 Circuit Fused Internal Distribution
FD4	4 Circuit Fused Internal Distribution
FD5	5 Circuit Fused Internal Distribution
FD6	6 Circuit Fused Internal Distribution
HTR	Internal thermostatically controlled battery heater (specify voltage)
IRT	Infrared Remote Test (specify AC voltage)
K5	1/2" Knockout for pendant mount
LCP	Less Canopy

Option	Description
LGD	Die Cast Lens Guard
LC	120VAC line cord
LD	Lamp Disconnect (internal)
PGD	Lexan Guard (separate order)
VS	Vandal resistant wraparound shield (separate order)
LT	Remote Laser Test (contact factory)
MC	Metal Canopy
MS	Mounting Shelf (separate order)
OBM	Octagon Box Mount (no line cord)
RFS	Radio Frequency Suppression (specify AC voltage)
SMH	Side Mounted Heads
OP	Special Wording
TD	Time Delay (specify AC voltage)
TFC	Teflon Coated Lens
TLP	Twist Lock Plug (specify AC voltage)
TSFN	Transfer Panel for AC & DC Exits
TSW	External Push Button Test Switch
HVC	Heavy-duty full width ceiling mount canopy
HVE	Heavy-duty full width end mount canopy
TP	Tamper Proof Screws
V	Voltmeter
TPX	Tamper Proof Torx Screw (Vandal Resistant Sign only)
VRF	Vandal Resistant Frame (Tritium sign)
WGD	Wireguard (separate order)

Glossary

Term	Description
IB	Self-powered for 90 minutes
IB1	Self-powered for 120 minutes
NDC	No DC backup voltage
UDC	Universal DC backup voltage from 6 to 24VDC