

Choose the right LED Downlight

All of our LED downlights are available in quick ship and certified Energy Star.



		LPDL - Low profile downlight		Swivel	Gimbal		Retro	Vivio	Presto	COMETO Commercial	CDU Gen 2
		Choice	Stanpro	Choice	Gimbal 7 W	Gimbal 12 W				Choice	
Main selling features		Ultra slim recessed downlight, less than 1" thick, perfect for shallow or constraint ceiling spaces		Directional downlight which can highlight specific zones with 360° rotation and up to 90° tilt	Small aperture and highly versatile design with directional light output	Outstanding performance, small aperture and recessed design with directional light output	Retrofit solution with E26 screw-in adaptor for existing recessed cans, easy installation	Dual installation offering both retrofit option or mounted directly into a 4" junction box	Quick installation with LED driver mounted directly on top of the light engine	Slim backlit commercial downlight with 5 CCT and 3 power selectables	All-in-one commercial downlight with integrated 3 CCT and 3 power selectable
Size(s) (in)		4, 6	3, 4, 6	4	3, 4	3.5	4, 5-6	4	4, 6	6, 8	4, 6, 8
Shape											
Watts (W)		11, 14	7, 9, 12	8, 9	7	12	10, 12, 15	8	7, 9	12/15/18 18/20/25	7/9/12 12/16/20 15/20/25
Lumen output (lm)		750, 1 100	Round: 500, 600, 820 Square: 450, 550, 780	Single CCT: 750 CCT Selectable: Up to 650	Warm Dim: 470 Single CCT: Up to 620	Warm Dim: 660 Single CCT: Up to 950 CCT Selectable: 850	Single CCT: 650, 850 CCT Selectable: 700, 1 100	650	550, 700	1 200/1 500/1 800 1 700/2 200/2 800	595/765/1 000 1 080/1 440/2 000 1 800/2 200/2 900
Volts (VAC)		120	120	120	120	120 120-277 ²	120	120	120	120-347	120-347
Color Temp. (K)	Single	3 000	2 700, 3 000, 4 000, 5 000	3 000	3 000, 4 000	3 000, 4 000	2 700, 3 000, 4 000		2 700, 3 000, 4 000		
	Warm Dim		3 000-2 200		3 000-2 200	3 000-2 200					
	Selectable	3 CCT: 2 700/3 000/4 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	3 CCT: 2 700/3 000/4 000		5 CCT: 2 700/3 000/3 500/4 000/5 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	3 CCT: 3 000/3 500/4 000
Color finish											
CRI		80+	80+	90+	80+, 90+	90+	90+	80+	80+	80+	80+
Beam angle											
Location											
Dimmable		ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	0-10 V ³	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	0-10 V	0-10 V
Cable rated		FT4	FT4, FT6	FT4	FT4	FT6				FT6	
Warranty (year)		5	7	5	5	5	5	5	5	5	5
IC rated		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Airtight		✓	✓	✓	✓	✓	✓	✓	✓	✓	
Other details		Available in a bulk pack of 10 units ¹			Interchangeable trims, increase flexibility and reduce inventory level Available in all-in-one kit either 3" or 4" in white	Available in individual bulk pack of 10 drivers and 10 LED modules for 2-phases job site deliveries ⁴		Black magnetic trim sold separately ⁵	Optional trim accessory finish White, Bronze, Silver and Black ⁵		

¹ Only available in 4" 30K white

² Only available with 5CCT selectable LED module

³ Only available with bulk pack option

⁴ Only available in 3.5" 30K white

⁵ Sold separately